

TECHNICAL DATESHEET

UHF TAGS

Speedo: UHF Windshield Tag

Product Code: WL06U



- UHF windshield tag is used in tracking all types of vehicles and parking management applications.
- It comes with heat-sustaining thin or foam adhesive for windshield application.
 Logo or text can be printed on top of the tag.

Technical Specifications:

Electrical: Operating Frequency:

Operating Mode:

Read Range:

(EU)865~868 MHz / (US)902~928 MHz Passive (battery-less transponder)

up to 6m* (Reader and antenna dependant)

Chip Type: Alien Higgs 3 EPC Class 1 Gen 2

EPC 96 bit extendable up to 480 bits

User Memory 512 bit

Data retention of up to 10 years

Mechanical: Dimension: 105 x 26mm (customized sizes available)

Material: Polyester with durable adhesive

IP rating: IP54

Thermal: Operating Temp. : -10°C to +55°C

Storage Temp.: -10°C to +45°C

Optional: Logo printing/Laser engraving at extra cost.

Preliminary Data Sheet: Certain specification subject to change.

<u>sales@wavelinx.in</u> <u>www.wavelinx.in</u>

Tel.: 011-25103930, 9911904826, 9911964826 • Email: sales@wavelinx.in • Website: www.wavelinx.in

^{*} Read-range achieved using standard testing methodology. Read range will vary with reader hardware and output power.