



LF TAGS

LF Proximity Label

Product Code: WL06L

F158EF

Employee Incident Line (EIL) : 0008004401540

Security Helpdesk - N2 : +91 9999083322
- N3 : +91 9711901823

Transport Emergency Helpline : +91 9711733462

Transport Helpline : +91 120 3895555

BMS - N2 : +91 120 4776122
- N3 : +91 120 3895003

Whistleblower : +91 120 3895151

- LF polyester label is designed for people tracking, access control and industrial production.
- It can be customized as per requirement with logo printing etc.

Technical Specifications:

Electrical: Operating Frequency:

Operating Mode : Read Range :

125 Khz

Passive (battery-less transponder) up to 50cms* (Reader and antenna

dependant)

Chip Type: TK4100/EM4200

64 bit read only

Data retention of up to 10 years

Mechanical: Dimension: 85 x 45 x 0.5mm

Material : Polyester IP rating : IP54

Thermal: Operating Temp. : -20°C to +55°C

Storage Temp. : -10°C to +50°C

Optional: Logo printing/Laser engraving at extra cost.

Preliminary Data Sheet: Certain specification subject to change.

sales@wavelinx.in www.wavelinx.in

^{*} Read-range achieved using standard testing methodology. Read range will vary with reader hardware and output power.