

SPEEDO

UHF Windshield Tag

UHF windshield tag is used in tracking all types of vehicles and in parking management applications.

It comes with heat-sustaining thin or foam adhesive for windshield application.

Logo or text can be printed on top of the tag.

It can be custom produced in different sizes as per customer requirement.



100% read-tested tags with industry best NXP UCode 8 chip. These tags can be customized with customer branding using digital printing.

RECOMMENDED APPLICATIONS

Vehicle Tracking

Speedo is designed to be easily applied on any vehicle windshield. It comes with a heat-sustaining thin film adhesive for easy application. Through RFID scanning, information can be received quickly and from a safe distance. WL06U is the optimal solution for your vehicle tracking and parking management needs.



SECURITY ASPECT

The tag is made up of special substrate that makes it 100% tamper-evident. So, it cannot be peeled-off from the windshield without tag getting damaged.

Specifications

| | |
|-----------------------|--|
| Part no.: | WL06U |
| Operating Frequency : | 840-960 MHz (GLOBAL) |
| Operating Mode : | Passive (battery-less transponder) |
| Read Range : | up to 10m* |
| Protocol : | ISO/IEC 18000-6C |
| Chip Type : | NXP UCode 8 EPC Class 1 Gen 2 |
| Memory : | EPC 128 bits TID 96 bits with 48 bits serial number User Memory 0 bits |
| Data retention : | Up to 10 years |
| Dimensions : | 105 x 26mm |
| Material : | Polyester with thin film adhesive |
| Ingress Protection : | IP54 |
| Operating Temp. : | -10°C to +55°C |
| Storage Temp. : | -10°C to +45°C |
| Colors : | White/Blue |
| Quality assurance : | 100% read-tested |
| Optional services : | Logo Printing and Encoding |

